**FEELUX** 

U Ν Α




## I Specification

Model Name FDA-P2M Rated Input 220-240V~50/60Hz 3A Rated Output Max. 600W Input Signal DMX512


Output Signal PWM 2CH (Max.10pcs per channel) Lighting Load DIMSLIM/DIMSLIMLINE

# Component & Wiring




## **I** Installation

- 1. Turn off the power before wiring
- 2. This interface is for Feelux Dimable Lighting. Please don't use with other dimable lighting.
- 3. L/N/P (Live Neutual and PWM signal) should be connected as specified. (L-Brown, N-Blue, P-Black)



### **DIP S/W SETTING INSTRUCTION**



# **I** Safety Precaution

Risk of Electrical Shock - More Than One Source of Supply - Disconnect All Power Sources Before Servicing

- Do not connect over Max,600W and Max, 10 pcs per channel
- Do not touch with wet hand. There is a chance of electric shock.
   Do not install this product close to flammables or heaters.
   Pull out the power cord in case of smoke or strange smell.
- Do not install at humid place or close to flammables.

- Do not disassemble or remodel this product.
  Do not pull fixed wires at the terminal. There is a chance of malfunction.
  Apply to Feelux Luminaire DIMSLIM/DIMSLIMLINE and Accessories only.
  - Do not use with other company's products.

## **I** Safety Precaution

Meaning of crossed-out wheeled dustbin: Do not dispose of electrical appliances as unsorted municipal waste, use separate collection facilities. Contact your local government for information regarding the collection systems available. If electrical appliances are disposed of in landfills or cumps, hazardous substances can leak into the groundwater and get into the foodchain, damaging your health and well-being. When replacing old appliances with new ones, the retailer is legally obligated to take back your old appliance for disposal at least free of charge.